

SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD (HCS) 29 CFR 1910.1200

Page 1 of 5

Revision Date Supersedes Date

9/14/2017 7/30/2015

SECTION 1. IDENTIFICATION

Product identifier: JAX Halo-Guard® NZ-LT

Part number: **HGNZLT**

Identified uses: Lubricant where there may be incidental food contact

Uses advised against: Not intended for direct food contact. Other uses advised against may be specified elsewhere in this SDS.

JAX INC Supplier:

> W134 N5373 Campbell Drive Menomonee Falls, WI 53051 USA

Email contact: info@jax.com

Non-emergency

Phone: 262-781-8850

contact: **INFOTRAC: Emergency telephone:**

> North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926

International 011-1-352-323-3500 (collect) China 400-120-0761

Fax: 262-781-3906

SECTION 2. HAZARD(S) IDENTIFICATION

Classification: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS

contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and

available for employees and other users of this product.

Label elements

Pictograms: Not applicable

Not applicable Signal word: **Hazard statements:** Not applicable **Precautionary** Not applicable statements:

Hazards not otherwise Not applicable.

classified:

Additional information: Not applicable

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	<u>Chemical name</u>	<u>%</u>	CAS #	<u>Impurities</u>
	White mineral oil (petroleum)	50-<70	8042-47-5	None
	Distillates (petroleum), solvent-refined heavy paraffinic*	10-<20	64741-88-4	None
	Calcium carbonate (dust)	5-<10	471-34-1	None
	Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts	1-<5	68584-23-6	None
	Calcium dodecylbenzene sulphonate	1-<3	26264-06-2	None
	Benzenamine, N-phenyl-, reaction products with 2,4,4-	1-<2.5	68411-46-1	None
	trimethylpentene			
	Sulfonic acids, petroleum, calcium salts	1-<5	61789-86-4	None

SECTION 4. FIRST-AID MEASURES

First aid measures

Eve contact: Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation

persists, consult a physican.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before

reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Ingestion:

Never give anything by mouth to an unconscious person. Consult a physician.

Page 2 of 5 JAX Halo-Guard® NZ-LT **Revision Date**

Supersedes Date

9/14/2017 7/30/2015

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention

immediately.

Most important

No further relevant information available.

symptoms and effects, both acute and delayed:

See First aid measures (above).

Indication of any immediate medical attention and special treatment available:

General information: No further relevant information available.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use direct stream of water. Water may be used to keep fire-exposed containers cool.

Unsuitable extinguishing media: Do not use direct stream of water.

Specific hazards:

Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool.

Advice for firefighters:

Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined

space or as otherwise needed.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

procedures:

Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

Methods for containment and cleaning up

Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.

Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Store away from oxidizing agents. Rotate stock.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits:

Chemical name Exposure limit and source White mineral oil (petroleum) 5 mg/m³ (oil mist), TWA, ACGIH Distillates (petroleum), solvent-refined heavy 5 mg/m³ (oil mist), OSHA

paraffinic*

Calcium carbonate (dust) TWA (respirable) = 5 mg/m^3 (NIOSH REL)

Benzenesulfonic acid, C10-16-alkyl derivatives, calcium

Not available

Calcium dodecylbenzene sulphonate Benzenamine, N-phenyl-, reaction products with 2,4,4-

trimethylpentene

Not available

Not available

Sulfonic acids, petroleum, calcium salts Not available

Exposure controls

Engineering controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapors below their respective

occupational exposure limits.

Ventilation: Use in a well-ventilated area. See Engineering Controls.

Page 3 of 5 JAX Halo-Guard® NZ-LT

Revision Date Supersedes Date

9/14/2017 7/30/2015

Personal hygiene: Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed

from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or

local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A

NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Gray semi-solid with mild petroleum odor **Upper flammability limit:** Not available Appearance / odor:

> Lower flammability limit: Not available

> > Not available

Negligible

Not available

Semi-solid **Physical state:** Vapor pressure: Not available

Odor threshold: Not available Vapor density:

Not available pH:

0.95 - 1.05 @ 20°C Melting / freezing point: Not available Relative density:

Initial boiling point Not available

and boiling range:

Flash point: **Partition coefficient** >356°F (180°C), ASTM D 92 Not available

(n-octanol/water):

Solubility in water:

Evaporation rate: Not available **Autoignition temperature:** Not available

Decomposition temperature: Not available

Flammability (solid, gas): Not applicable Viscosity: Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions. **Chemical stability:** Stable under recommended conditions.

Possibility of

hazardous reactions:

Hazardous reactions are not expected to occur. **Conditions and** Avoid heat, open flames, strong acids, strong bases, and oxidizing materials.

materials to avoid:

Hazardous Carbon monoxide, carbon dioxide, oxides of sulfur, oxides of calcium, smoke and irritating vapors as products of incomplete

products:

decomposition combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

No known significant effects or critical hazards. Eye contact: Skin contact: No known significant effects or critical hazards. Inhalation: No known significant effects or critical hazards. No known significant effects or critical hazards. Ingestion:

Component Components <u>LC</u>50 LD₅₀

information: White mineral oil (petroleum) >5000 mg/kg (oral, rat) Not available

Distillates (petroleum), solvent-refined heavy

paraffinic*

Calcium carbonate (dust) Not available Not available

Not available

Benzenesulfonic acid, C10-16-alkyl derivatives, calcium Not available Not available

salts

>4199 mg/kg (dermal, rabbit) Not available Calcium dodecylbenzene sulphonate

Benzenamine, N-phenyl-, reaction products with 2,4,4->2000 mg/kg (oral, rat) Not available

trimethylpentene

Sulfonic acids, petroleum, calcium salts >5000 mg/kg (oral, rat) Not available

Page 4 of 5 JAX Halo-Guard® NZ-LT

Revision Date Supersedes Date

9/14/2017 7/30/2015

Symptoms: See Section 4 of this SDS for symptoms.

Delayed and immediate effects, and chronic effects, from short and long-terms exposure

Effects: No further relevant information available.

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

Numerical measures of

toxicity:

Not determined

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: Not available

L(E)C₅₀ Component Components information: White mineral oil (petroleum) Not available

Distillates (petroleum), solvent-refined heavy

paraffinic*

Calcium carbonate (dust) Not available Benzenesulfonic acid, C10-16-alkyl derivatives, calcium Not available

salts

Calcium dodecylbenzene sulphonate Benzenamine, N-phenyl-, reaction products with 2,4,4-

trimethylpentene

Not determined

Sulfonic acids, petroleum, calcium salts >100 mg/l/48h [Daphnia magna (Water flea)]

Not available

2.5 mg/l/48h [Daphnia magna (Water flea)]

>71 mg/l/96h [Danio rerio (zebra fish)]

Persistence and

Waste treatment

degradability:

Bioaccumulative Not determined

potential:

Mobility in soil: Not available Other adverse effects: Not determined

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. methods: Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

Dacking

	Proper Shipping Name:	UN Number:	Class:	Groups	Remarks:
	rroper simponing ivanie.	ON NUMBER.	Class.	Group:	itemarks.
U.S. D.O.T.	Not regulated	None	None	None	None
ADR/RID	Not regulated	None	None	None	None
<u>IMDG</u>	Not regulated	None	None	None	None
<u>IATA</u>	Not regulated	None	None	None	None

SECTION 15. REGULATORY INFORMATION

U.S. Federal Regulations

This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List: SARA Section 302

Extremely Hazardous None

Substances:

SARA Section 304 **CERCLA Hazardous** Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to

reporting to the National Response Center under CERCLA:

Substances: Calcium dodecylbenzenesulphonate, CAS # 26264-06-2, RQ = 1000 lbs.*

*Calculated RQ exceeds reasonably attainable upper limit.

Chemicals:

SARA Section 313 Toxic This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations:

TSCA Inventory: All components of this material are on the U.S. TSCA Inventory.

U.S. State Regulations

JAX Halo-Guard® NZ-LT
Page 5 of 5
Revision Date

Revision Date
Supersedes Date

9/14/2017 7/30/2015

California Proposition

This product does not contain chemical(s) known to the State of California to cause cancer, birth defects, or other

reproductive harm.

None

California
Proposition 65

Listed Components:

International Regulations

Canada: This product has been classified in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the

information required by those regulations.

Japan MITI:

Australia:

Not available

Not available

Not available

SECTION 16. OTHER INFORMATION

Sections Revised: Sections 2, 3, 4, 9, 11 and 12.

Revision Date: 9/14/2017

The information and recommendations contained herein are, to the best of JAX INC's knowledge and belief, accurate and reliable as of the date issued. JAX INC makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with JAX INC's interpretation of the available data.

*** END OF SDS ***